



NOEL LESLEY

PORT A COOL OPERATING REQUIREMENTS

START UP

1. Position unit on stable, level surface and set caster brakes.
2. Attach water hose and fill sump
3. Start pump **10 minutes** before fan. **DO NOT RUN PUMP WITH EMPTY SUMP.**
4. Start fan. (**Do not move unit with fan running**).

SHUTDOWN

1. Stop pump **15 minutes** before stopping fan.
 2. Stop fan when pads are dry.
- Do not operate unit with a damaged cord or plug.
 - Do not run electrical cord under any carpeting or cover with throw rugs, runners, or similar coverings.
 - Arrange cord away from foot traffic area or use cable ramps to cover.
 - Plug unit into three-prong grounded GFCI protected electrical receptacle only.
 - Do not step on or roll over power cord with heavy or sharp objects.
 - Do not operate unit unless all pads are securely in place and the unit is upright.
 - Remove plug from electrical receptacle by pulling on the plug and not the cord.
 - Test GFCI receptacle or breaker to ensure it is functioning properly.
 - Do not operate near open containers of flammable liquids or gases. A distance of at least 35 feet away from open flame or sparks is required.
 - Do not wash unit cabinet with water as it will harm the motor and electrical system.

I have read and understand the above instructions for Port A Cool operation.

Customer Signature

Date

Print Name